

Recorders SRT-600P (Specification)

Cassette Type Standard 1/2" VHS (E-180)

Video Recording System	4 Head, 2 Video helical heads for recording and standard play back, Helical scan heads for Special playback
RECORDING SYSTEM	Luminance FM recording
Colour	Rotary phase converted sub carrier, direct recording
Recording and playback time	8, 24H
Audio recording	8, 24 - hour mode
High speed scan	7X (3 hours modes)
Rewind / FF time	Approx. 5 minute (with E-180)
VIDEO Signal format	CCIR Standard 625 lines, 50 fields/ sec. CCIR Black and White, PAL colour auto select
Video input	1.0 Vp-p 75 ohm unbalanced
Video output	1.0 Vp-p 75 ohm unbalanced
Horizontal resolution	350 lines (B/W) 240 lines (Colour)
Signal to noise ratio	45dB
AUDIO Input	Ground contact closure
Output	+ 5 volts at 5.7k ohms
Microphone input	Mini phono jack (3.5mm)
TIME/DATE GENERATOR	1st line Day, Month, Year, Weekday, Alarm, Count 2nd line Hour, Minute, Second, Recording speed
Format	24 hour
Battery backup	30 days
ALARM COMMANDS Input	Ground contact closure
Output	+ 5 volts at 5.7k ohms
CONNECTORS Video in/out	BNC
Audio in/out	RCA phono jack
Microphone input	Mini phono jack (3.5mm)
Remote control	Mini phono jack (3.5mm)
Tape end out	Screw type terminal strip
Alarm in/out	Screw type terminal strip
Switch output	Screw type terminal strip
Timer output	Screw type terminal strip
Warning output	Screw type terminal strip
Clock set input	Screw type terminal strip
Clock set output	Screw type terminal strip
External timer input	Screw type terminal strip
Eject input	Screw type terminal strip
Eject output	Screw type terminal strip
Dimensions (W x H x D)	360 x 91 x 338 mm
Weight	Approx. 4.9kg
Operating temperature	5C-40C
Power	220V-240V AC,50Hz
Power consumption	Approx. 20W